



DTI SmartFloor Maintenance SOP







- 1) Attach <u>blue pad</u> on driver and lock with Velcro pad holder lock
 - Scrubber discs will face the ground
 - <u>Blue pad</u> should be used for daily scrubbing
- 2) Install driver with blue pad on scrubber
- 3) Fill scrubber with water and add "DTI Rejuvenating Cleaner" while wearing protective goggles and gloves.
 - Ensure tank is fully drained prior to start

Scrubber Model	Cleaner
Ride-on	4 pumps
Walk-behind	1 pump





DTI SmartFloor Maintenance SOP







- 4) Scrubber settings:
 - Drive Speed: MEDIUM
 - Pressure: MEDIUM
 - Water: LEVEL 2
 - Do not run in "ECO" mode

- 5) The entire warehouse should be scrubbed with the **blue pad** daily.
- Results will be achieved over time with twice daily scrubbing (AM & PM)
- Result timeline will vary based on initial condition of concrete
- 6) Expected results with daily scrubbing:
- Stains will diminish over time
- Improved gloss retention
- Increased stain resistance






DTI SmartFloor Maintenance SOP



- 7) Remove the driver and **blue pad** after each shift:
- Remove the driver from the scrubber
- Remove the pad from the driver



- 8) Pad cleaning
- Remove any foreign debris from pad
- Thoroughly rinse with water
- Hang up to dry
- ***Thorough cleaning will extend pad life***



- 9) Pad Replacement
- Replace when the colored line (blue or orange) is no longer visible
- A set of blue pads should last 1 week





DTI SmartFloor Maintenance SOP









dtindustrialflooring.com/re-order-smartfloor/

- 10) Fully drain all waste water after each cleaning
- 11) Notes
 - Do not scrub over polymer flooring
 - Do not run scrubber in "Eco" mode
 - The <u>orange pad</u> should only be used for heavy stains. They are available only for the walk-behind scrubber when individual stains need attention.

DTI Account Representative:

Michael Cavanaugh michael@dti-cs.com Cell: (856) 879-5392 Office: (209) 879-9814